

# Scudoband Adesivo



**Self-adhesive butyl rubber band for sealing and waterproofing joint areas between horizontal and vertical surfaces.**



**Fields of application:**

- elastic waterproofing of perimeter joints between wall and floor;
- for sealing the joint corner between floor slab and wall;

- for application on bitumen surfaces, PVC, wood, polycarbonate and plastic material;
- professional use only.

**Characteristics:**

**Scudoband Adesivo** is an exclusive band in butyl rubber, combined with a non-woven fabric. **Scudoband Adesivo** is an indispensable product in every waterproofing situation. Its versatile use enables to join waterproofing made with **Scudo A+B**, **Scudo Revolution**, **Sanigum**, **Scudo Protech** with materials such as iron, PVC, PPE, HDPE and bitumen membranes, finally solving possible seepage causes. Indicated for indoor and outdoor civil, commercial and industrial applications.

**Application:**

remove the protective silicon tape from the back of the **Scudoband Adesivo**. Then position the band so that is it half on the vertical surface and half on the horizontal surface, pressing down firmly to make sure it sticks. When spreading the **Sanigum** or **Scudo** waterproofing coat, remember to take it a few centimetres higher than the **Scudoband adesivo**.

**Preparation:**

The base must be sound, flat, compact, have no parts coming away, and be free of dust, grease, oil, paint and wax. The base must be dry and well established. Provide the laying surface with protection from direct sunlight beforehand.

**Quality and Environmental Standards:**

**Scudoband Adesivo** undergoes constant, careful testing at our laboratories, in compliance with the legislation in force - UNI EN ISO 9001/2015.

Characteristics	Application methods	Consumption
Applic. temperature: from +5°C to +35°C Longitudinal break: 29 N/15 mm Cross break: 23 N/15 mm Resistance to acids: excellent Resistance to humidity, alkalis, oils and ageing: excellent Resistance to temp.: from -30 to +70°C Resistance to water pressure: 0.2 bar Resistant to alkalis Horizontal and vertical installation Final side elongation: 100% Total weight: 1000 g/m <sup>2</sup>	Manually	Depending on the surface  <b>Storage</b> Quality and characteristics remain unchanged for a long time. It is anyway recommended to use the product within 12 months.

Code	Product	Form and color	Packages	Pallet
406143	Scudoband Adesivo	Grey elastomer	15 m x 10 cm single package	100 pcs

**Warning**

- do not use for diving joints;
- do not use in areas subject to rising damp;
- if the laying surface is porous, apply a coat of **Primer GS**.



**Technical and application specifications**

Hazard classification as per Directive 99/45/EC:	<b>none</b>
Application temperature:	<b>from +5°C to +35°C</b>
Height:	<b>7.5 cm</b>
Total weight:	<b>1000 g/m<sup>2</sup></b>

**FINAL PERFORMANCE SPECIFICATIONS**

Water pressure resistance:	<b>0.2 bar</b>
Tensile stress at break (long.):	<b>29 N/15 mm</b>
Tensile stress at break (cross.):	<b>23 N/15 mm</b>
Elongation at break:	<b>100%</b>
Acid resistance:	<b>excellent</b>
Resistance to damp, solvents, oil, alkalis and ageing:	<b>excellent</b>
Temperature resistance:	<b>from -40°C to +70°C</b>
Harmonised customs code:	<b>39191080</b>

Measurement of data at 23°C/50% Residual Humidity and no ventilation.  
The data may be considerably modified by the conditions of use.